

>>> RP-1600W



RP-1600W 16-P Smart Access Web Management Switch



This switch provides the utility to auto-discover the S.A.W.M. series switch from LAN side. The administrators are able to access and manage the network anytime, anywhere, no need to stand by those switches and configure them via the console port anymore.

By exclusively browsing utility, MIS staffs don't need to keep notes and pencils, to have a clearly picture between IP address and real switch location. And just with one Real gateway IP address, now you can access and manage your switches with assigned Private IP from WAN side.

FEATURES

- Supports Auto-Negotiation on each TP port
- Bridging capability for 100Mbps and 10Mbps segments.
- Provides Store-and-Forward forwarding scheme.
- Supports Auto MDI/MDIX function
- IEEE 802.3x Flow-Control supports for Full-Duplex operation
- Back-Pressure function supports for Half-Duplex operation
- Support 16 Groups VLAN and two queues plus TOS for multi-media application

SPECIFICATIONS

Standards	• IEEE 802.3 10BASE-T • IEEE 802.3u 100BASE-TX • IEEE 802.3x Flow Control for Full-Duplex Operation
Forwarding/Filtering Rate	• 14880 packets/second per port @ 10Mbps, max • 148800 packets/second per port @ 100Mbps, max
Configuration Interface	• IE Web browser
Auto-MDI	• All TP ports support Auto-MDI/MDI-X Function
Reset Button	• Reload IP, User Name and Password to default value
LED Indicators	• One (1) for Power • One (1) per port for Link/ACT • One (1) per port for Full-Duplex or Collision
Environment	• Operating Temperature: -20°C ~ 45°C (-4°F ~ 113°F) • Storage Temperature: -40°C ~ 80°C (-40°F ~ 176°F) • Humidity: 10% ~ 90% Non-condensing
Power Supply	• Internal full range switching power supply • Input voltage: 100 ~ 240 +10%V AC 50/60 Hz
Dimensions	• 442 x 185 x 44 mm
Certifications	• CE, FCC